Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VALVOLINE $ATF + 4^{TM}$

Valvoline ATF + 4[™] is a uniquely blended automatic transmission fluid that meets Chrysler Material Standard MS-9602. It is designed as a factory fill fluid for all 1998 and later Chrysler Corporation automatic transmissions and transaxles. It is fully compatible with all transmissions that require Mopar ATF +®, Mopar ATF+2[™] and Mopar ATF+3[™]. Valvoline ATF + 4[™] is for use in all applications specifying Mopar ATF+4 or Type MS-9602 fluid.

The Valvoline ATF + 4™ Advantages:

- Longer Life: Improved thermal stability for longer fluid life.
- Better Viscosity Stability: Improved viscosity stability for consistent transmission operation.
- Frictional Enhancement: Specific fricitonal properties for smooth clutch engagement.
- Corrosion & Wear Protection: Contains special additives to prevent rust corrosion and wear for longer life.
- Foaming Protection: Contains additive to reduce foaming.

Performance Level

Mopar ATF+ MS 7176® Mopar ATF+2® MS 7176 Mopar ATF+3™ Mopar ATF+4™

Test	Typical Property	
Viscosity @ 100C, cSt	7.55	
Viscosity @ 40C, cSt	34.13	
Viscosity Index	198	
Specific Gravity @ 60F	0.8506	
Density, lbs/gal	7.09	
Pour Point, C, max.	-48	
Zinc, wt.%	Nil	
Calcium, wt.%	0.069	
Phosphorus, wt.%	0.046	
Boron, wt.%	0.014	
Brookfield Viscosity @ -40C, cP	9,000	
Flash Point, COC, C	196	

Effective Date: 10/26/2011 Replaces: 10/23/2005 Alexey Stiop Doc #-02