

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VALVOLINE DURABLEND GREASE

DuraBlend Grease is a semi-synthetic lithium complex EP heavy-duty automotive grease with exceptional resistance to high temperatures and heavy loads. It is recommended for a wide range of industrial and automotive use including wheel bearings of disc-brake equipped vehicles, chassis lubricant, suspension systems, universal joints, steering linkage and constant velocity joints.

Character: Smooth, buttery, water repellent, oxidation & rust inhibited, extreme pressure

Approvals/Performance Levels

General Motors Part No. 1051344 (which supersedes GM Part No. 1051195)

NLGI GC- LB

MACK GC-G

Typical Properties

NLGI Grade	2
Soap Base	Lithium Complex
Color	Gray-Black
ASTM Worked Penetration @ 77°F	275
ASTM Dropping Point, °F	530
Kinematic Vis @ 40° C, cSt	124.6
Kinematic Vis @ 100° C, cSt	13.5
Viscosity Index	105
Pour Point °C	-12
Timken OK Load, lbs min	45

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:
11-1-11

Replaces:
8-14-06

Author's Initials:
DJD

Code
Rev 002