Product Information

Valvoline.

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC.

Valvoline[™] Premium Blue[™] GEO

Valvoline's Premium Blue GEO 15W-40 is recommended for use in urban bus, delivery truck and other service fleets fueled by CNG (compressed natural gas) and LNG (liquefied natural gas). It is formulated with premium quality Gr II basestocks and additive components to provide excellent protection against oxidation, nitration, wear, deposits and provide outstanding lubrication of gaseous fueled engines. The ash content of the oil is optimized to improve performance for long drain application. This product is recommended for Cummins B&C, Detroit Diesel, Volvo/Mack and Mercedes-Benz dedicated natural gas engines for vehicular applications. For other engines, please refer to engine manufacturer's specifications.

Product is approved against Cummins CES 20074, Detroit Diesel 93K216 and for Volvo CNG powered commercial engines; Meets performance requirements of API CF-4 and suitable for use in engines that call for MB 226.9.

Premium Blue GEO Advantages:

- Extensively tested in different CNG/LNG fueled engines
- Optimized ash level for long drain capability
- Valve recession protection

Part Numbers

- Low oil consumption and piston deposit control
- Enhanced valvetrain wear protection
- Advanced oxidation resistance

Typical Properties	SAE 15W-40
Specific Gravity	0.876
Viscosity @ 40° C, cSt	120.36
Viscosity @ 100° C, cSt	15.5
Viscosity Index	135
CCS Viscosity @ -20° C, cP	6500
Pour Point, °C	-39
Flash Point, COC, °C	220
Total Base Number (D-2896)	6.2
Sulfated Ash, Wt. %	0.88
Foam Test	Pass

Endorsed and Recommended by Cummins Inc.



Bulk	VV705200
55 Gallon Drum	VV70520
5 Gallon Pail	VV70521
3/1 Gallon Jug	774039
Tote	853218

Refer to Valvoline's Material Safety Data Sheet for health and safety instructions

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date: Expiration Date: Replaces: Author's Initials: Code 08/04/2014 N/A 5/1/2013 JF 1401

