

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants – Industrial Lubricants- Hydraulic Oil

Version: 2167, 2168/03

Valtac

Premium Mineral Slideways Oil

- Reduces wear and friction

Valvoline Valtac product range is designed for the lubrication of machine tool slideways. This unique product contain tackifiers and extreme pressure additives which reduce friction and maintains film strength under heavy loads and slow movement. Are recommended for slideway, both horizontal and vertical lubrication.

Valvoline Valtac product range is also recommended for precision machinery where slow feed rates are required. Suitable for gears of feed mechanisms, lead screws-nut applications.

Meet the requirements of Cincinnatti Milacron Specifications P47 (ISO 68) and P50 (ISO 220).

Specifications and Approvals

Approvals/Performance Levels

Cincinnatti Milacron Specifications
P47 (ISO 68) and P50 (ISO 220).

¹ Check owners' manual before use.

Applications

They are available in ISO Grades from 68 to 220

Please consult the owners' manual before use.

Features and Benefits

- Viscosity Control

Delivers enhanced durability

- Wear protection

The advanced extreme pressure additives ensures excellent wear protection and enhances component life

- Superior Water Separation

Very good demulsibility performance for longer fluid life and rust prevention

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

<i>Valtac</i>	68	220
Viscosity @ 100 °C, mm ² /s, ASTM D445	9.4	20.0
Viscosity @ 40 °C, mm ² /s, ASTM D445	68	220
Viscosity Index, ASTM D2270	116	101
Density @ 15C, kg/L, ASTM D4052	0.869	0.891
Flash Point (COC), °C, ASTM D92	254	
Pour Point, °C, ASTM D5950	-33	

This information only applies to products manufactured in the following location(s): Australia

68	220	Pack Size
2167.20	2168.20	20L
2167.51	2168.51	205L

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658

Author:

FM – Effective 1-04-2013

Replaces – 2167, 2168/02